



United Chemicals

TECHNICAL DATA SHEET
Ed.1 Rev: Jan 2020

UNIOIL NFS

Sulphited natural and vegetable oils

TYPICAL PROPERTIES

Appearance	: Light brown liquid
Active Substance	: 60 ± 1%
pH (10% sol.)	: 7.0 ± 0.5
Ionic Character	: Anionic

DESCRIPTION

UNIOIL NFS is a versatile fatliquor which improves tear/stitch and tensile strength and light resistance properties of leathers. It has excellent emulsion stability, better lubrication ability with deep penetration capacity, which makes it an outstanding product for chrome, semi-chrome, chrome, retan and vegetable tanned leathers. **UNIOIL NFS** can be applied even in tanning and retanning phases with high bath exhaustion.

APPLICATION

UNIOIL NFS can be used 4 - 6% for semi-chrome leathers; 2 - 4% for upholstery; 2 - 3% for chrome upper and 4 - 6% for light vegetable tanned leathers with addition of appropriate other **UNIOIL** fatliquors.

PACKAGING, STORAGE AND SHELF LIFE

Available in 120 kg drums or in IBC. Store in accordance with local regulations. Keep the lid closed when not in use. Store in a dry place and protect from direct sunlight. Shelf life is 12 months from the date of manufacture when stored in its original package. For more information see Safety Data Sheet.