



United Chemicals

TECHNICAL DATA SHEET

Ed.1 Rev: Jan 2020

# UNITAN A-55

Cyclic paraldehyde based tanning agent

## TYPICAL PROPERTIES

Appearance	: Amber liquid
Solid Content	: $36 \pm 2\%$
pH (10% sol.)	: $10.0 \pm 0.5$
Ionic Character	: Anionic

## DESCRIPTION

**UNITAN A-55** helps in obtaining higher chrome exhaustion and yields more uniform tanning process with fuller and softer leather. **UNITAN A-55** yields brilliant dyeing and better fastness properties.

## APPLICATION

**UNITAN A-55** can be used in different production phases of double-face productions, such as 0.2 - 0.5 g/l in soaking for fixing the wool roots; 1 - 2 g/l in pickling, after basification and neutralisation. Also, for sheep-garment and shoe-upper leathers 1 - 2% in pickling, after basification and neutralisation process phases are suggested for better fastness properties.

## PACKAGING, STORAGE AND SHELF LIFE

Available in 120 kg drums or in IBC. Store in accordance with local regulations. Keep the lid closed when not in use. Store in a dry place and protect from direct sunlight. Shelf life is 12 months from the date of manufacture when stored in its original package. For more information see Safety Data Sheet.